



OILPRO™ BOSS HEAVY DUTY TRACTOR HYDRAULIC FLUID J20C is specifically designed for lubrication requirements for tractor transmissions and drive gears that meets or exceeds the requirements of John Deere Specification J20C. It is formulated with high quality base stocks resulting in improved oxidation resistance, viscosity retention, and cold flow properties. This fluid is designed to function as a multi-functional hydraulic /transmission fluid that also can be used for power steering, power brake, power take-off, and implement drive fluid. OILPRO BOSS Tractor Hydraulic Fluid (J20C) is a balanced formulation that provides excellent corrosion protection and oil oxidation stability at all service temperatures.

**TYPICAL PROPERTIES**

PRODUCT NAME	J20C
Density (lb/gal)	7.169
Density (g/mL)	0.8599
API Gravity	33.1
Kinematic Viscosity	
mm <sup>2</sup> /s @ 40C	56.33
mm <sup>2</sup> /s @ 100C	9.50
Viscosity Index	152.5
Flash Point , C (F)	>200 C (392F)
Pour Point, C (F)	-39 (-38)

**BENEFITS**

- Exceptional performance characteristics to maintain seals and gaskets
- Unmatched thermal & oxidation stability
- Advanced anti-wear chemistry for complete protection of transmissions, axles and hydraulic pumps
- Enhanced formulation enables use in both hydraulic systems and tractor transmissions

**PRODUCT APPLICATIONS & SPECIFICATIONS**

**MEETS THE REQUIREMENTS OF:**

**John Deere Quatrol J20A, J20C**

**Allis Chalmers PF 821 XL**

**Allison (ATD) C-3 (UTD)**

**Caterpillar TO-2**

**International Harvester B-6 (Hy-Tran)**

**HYDRAULIC SYSTEM SPECIFICATIONS:**

**Denison KIOTA HF-0, HF-1, HF-2, Eaton Hydraulics**

**Komatsu Vickers I-2986-S, M-2950-S**



2586 SOUTHPORT ROAD, SPARTANBURG, SC 29302  
1-800-922-3149