

LubriGold[®] Full Synthetic SAE 0W-20 dexos1[®] Motor Oil

LubriGold Full Synthetic SAE 0W-20 dexos1® **Motor Oil** is top tier, high detergent automotive engine oil specially formulated to meet the stringent lubrication requirements of today and tomorrow's engines. It meets API SN which is required for 2012 and later engines. Synthetic base oils combine with carefully selected additive packages to provide maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish.

LubriGold Full Synthetic SAE 0W-20 dexos1® **Motor Oil** is specifically formulated to deliver increased fuel economy, and protection from frequent re-starts that occur in some hybrid vehicles. The science of using synthetic base stocks in SAE 0W-20 viscosity grade translates into outstanding engine protection when operating in both high and low temperature environments.

LubriGold Full Synthetic SAE 0W-20 dexos1® **Motor Oil** is a licensed GM dexos1® product (GM License # RB1D0726028). Meets or exceeds API Service Category SN, SM, SL, SJ and ILSAC GF-5 requirements. Exceeds the performance requirements of Toyota and Honda.

Benefits

- Formulated to reduce friction and provide increased fuel economy
- Protects engine in all temperatures and conditions
- Keep precision parts running clean
- ILSAC GF-5 Resource Conserving



Warren Oil Company, Inc



LubriGold[®] Full Synthetic SAE 0W-20 dexos1[®] Motor Oil

Typical Characteristics:

SAE Grade	0W-20
API Gravity @ 60°F	36.15
Sp. Gr. @ 60°F	0.8440
Flash, COC, °F	460
Pour Pt., °F	-50
Viscosity,	
cSt @ 40°C	44.4
cSt @ 100°C	8.6
Viscosity Index	175
Zinc, Wt. %	.0829
Phosphorus, Wt. %	.0752
API Performance	SN
Blend Site	AR
GM dexos1 [®] License Number	RB1D0726028
Part Number	
Bulk	25000



Warren Oil Company, Inc