



Coastal[®] Synthetic Blend GF-5 Motor Oil

COASTAL SYNTHETIC BLEND GF-5 MOTOR OILS are premium-quality, high detergent automotive engine oils specially formulated to meet the stringent lubrication requirements of today's engines. A unique blend of synthetic and high viscosity index Group II mineral oils combined with a carefully selected additive package, provide maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish deposits. API SN PLUS helps prevent pre-ignition and wear, and provides improved cleanliness and fuel economy.

COASTAL SYNTHETIC BLEND GF-5 MOTOR OILS meet or exceed the requirements of GM 6094M (SAE 5W-20, 5W-30, 10W-30) and Ford WSS-M2C945-A (SAE 5W-20) and WSS-M2C946-A (SAE 5W-30), Chrysler MS-6395 (SAE 5W-20, 5W-30, 10W-30). Meets Toyota Specifications, and Honda Service Fill Specifications (SAE 5W-20, SAE 5W-30 and SAE 10W-30).

All grades meet or exceed API Service Category SN Plus, SN, SM, SL, or SJ and comply with ILSAC GF-5 requirements.

Benefits

- Improved fuel economy
- Increased sludge protection
- Enhanced piston cleanliness
- Increased emission protection
- ILSAC GF-5 Resource Conserving formula



Warren Oil Company, LLC

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301



Coastal[®] Synthetic Blend GF-5 Motor Oil

Typical Characteristics:

COASTAL SYNTHETIC BLEND GF-5 MOTOR OIL			
SAE Grade	5W-20	5W-30	10W-30
API Gravity @ 60°F	33.4	33.1	30.1
Sp. Gr. @ 60°F	.8581	.8595	.8702
Flash, COC, °F	428	420	430
Pour Pt., °F	-38	-38	-30
Viscosity, cSt @ 40°C	50.3	60.8	68.2
Viscosity, cSt @ 100°C	8.6	10.2	10.3
Viscosity Index	149	156	137
API Service Category	SN PLUS	SN PLUS	SN PLUS
ILSAC	GF-5	GF-5	GF-5



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301