



OILPRO™ DEXRON®-III MERCON® MULTI-PURPOSE ATF

OILPRO™ MULTI-PURPOSE TRANSMISSION FLUID is an automatic transmission fluid formulated to meet the needs of high performance, multi-purpose, power transmission fluid requirements. It is designed for use in passenger car and light truck automotive transmissions. It is a blend of high quality base oils and premium additives that provide outstanding oxidation and thermal stability, friction control, load-carrying ability, corrosion and wear protection as well as preventing the accumulations of deposits and the formation of sludge, varnish, and foam. It is especially effective in reducing and minimizing annoying transmission "chatter", and provides fast circulation during cold weather and excellent lubrication and performance when hot.

TYPICAL PROPERTIES

API GRAVITY	ASTM D4052	35.6
VISCOSITY	ASTM D445	
@40C, cSt		31.8
@100C, cSt		6.3
VISCOSITY INDEX	ASTM D2270	153
BROOKFIELD VISCOSITY, cPs	ASTM D2983	
@-40C		11,240 cP
POUR POINT	ASTM D97	<-42 C
COLOR	ASTM D5100	RED

FEATURES & BENEFITS

- Universal unlicensed product that meets prior GM/Ford ATF standards.
- Allison C-4 and other applications calling for use of DIIIH/M quality ATF.
- Provides quiet shifting.
- Reduces wear of critical parts.
- Reduces maintenance costs and extends transmission life.
- Outstanding thermal stability and oxidation resistance.
 - Eliminates transmission noise and vibration.
 - Inhibits foaming.
 - Protects transmission against rust, corrosion and varnish

2586 SOUTHPORT ROAD, SPARTANBURG, SC 29302
1-800-922-3149

