



OILPRO™ ULTIMATE HIGH MILEAGE MOTOR OILS are formulated using high-quality Group II+ base oils and specific performance additives designed to help stop leaks and reduce oil consumption by conditioning seals and gaskets while reducing sludge and deposits. This proprietary formula is specially engineered for vehicles with over 75,000 miles and to meet or exceed the latest demands of turbocharged gasoline and propane engines in passenger cars and light duty trucks.

APPLICATIONS

| OILPRO ULTIMATE HIGH MILEAGE meets or exceeds the requirements of: | HIGH MILEAGE 5W30 | HIGH MILEAGE 10W30 |
|--|-------------------|--------------------|
| API SN Plus Resource Conserving | ✓ | ✓ |
| API SN Plus | ✓ | ✓ |
| API SN | ✓ | ✓ |
| API SN Resource Conserving | ✓ | ✓ |
| ILSAC GF-5 | ✓ | ✓ |
| ILSAC GF-4 | ✓ | ✓ |
| GM 6094M | ✓ | ✓ |
| FORD WSS-M2C 946-B1 (5W-30) | ✓ | |

BENEFITS

- Complete Engine Shield Protection Technology
- Improves Gas Mileage by keeping engine exceptionally clean & reducing friction
- Ultimate Performance in extreme temperatures, providing faster oil flow in cold temps and unmatched protection in extreme heat
- Enhanced detergent and dispersant to help reduce deposits, sludge & varnish formation

TYPICAL PROPERTIES

| SAE GRADE | 5W-30 | 10W-30 |
|---------------------------|-----------|-----------|
| Kinematic Viscosity | | |
| mm ² /s @ 40C | 64.5 | 65.0 |
| mm ² /s @ 100C | 10.7 | 10.2 |
| Viscosity Index | 157 | 144 |
| CCS Viscosity | | |
| cp @ -30C | 5,400 | - |
| cp @ -25C | - | 5,100 |
| MRV Viscosity | | |
| cp @ -30C | - | 15,000 |
| cp @ -35C | 21,000 | - |
| TBN | 7.3 | 7.3 |
| NOACK, wt% | <15 | <15 |
| Flash Point, C (F) | 204 (399) | 206 (403) |
| Pour Point, C (F) | -39 (-38) | -42 (-44) |

