OILPRO FULL SYNTHETIC API SP/GF-6A MULTI-GRADE ENGINE OILS SAE 0W-16, 0W-20, 5W-20, 5W-30, 10W-30

PRODUCT DESCRIPTION

OILPRO Full Synthetic Motor Oil is our most advanced full synthetic passenger car & light-duty truck engine oil series. Formulated with premium high quality OILPRO base stocks and compounded with a state-of-the-art advanced additive package that delivers superior protection and performance in extreme temperature ranges.

PRODUCT APPLICATION

OILPRO Full Synthetic Motor Oil is recommended for use in a wide range of vehicle and fuel types requiring approved fluids:

• Gasoline and flex fuel (up to E85) passenger cars, light-duty trucks, sport utility vehicles and gasoline-electric hybrids.

• Safely protect engines fitted with turbochargers (including TGDI engines), superchargers & emission control system catalysts.

• Engines and manufacturers specifying an API SP/ILSAC GF-6A approved engine oil.



ILSAC GF-6A

SPECIFICATIONS

- API SP, SN Plus, SN
- Ford WSS-M2C962-A1
- C962-A1 Chrysler MS-6395 • GM 4718M & GM 6094M
- Ford WSS-M2C947-B1
- Ford WSS-M2C946-B1

TYPICAL TECHNICAL PROPERTIES



FEATURES AND BENEFITS

OILPRO Full Synthetic Motor Oils are formulated to surpass API SP & ILSAC GF-6A industry standards in order to meet the ever-increasing performance and emissions requirements of today's technologically advanced engine systems:

• Protects Turbocharged Gasoline Direct Injection (TGDI) engines that may experience Low-Speed Pre-Ignition (LSPI).

- Improved control of sludge, high temperature deposit formation and viscosity increase than previous generation gasoline engine oils.
- Robust anti-wear & friction control additives help protect timing chains and valvetrains from stretching and surface degradation.
- Maintains more consistent viscosity than previous generation chemistry which helps extend both drain intervals and engine life.
- Helps reduce fuel costs while still providing excellent protection against engine wear under the most extreme operating conditions.
- OILPRO Full Synthetic engine oils are backward compatible to previous API and ILSAC specifications.

MADE IN T	HE 🐘

UDI	

PROPERTY	0W-16	0W-20	5W-20	5W-30	10W-30
Viscosity @ 40°C (cSt)	37.0	39.87	40.36	63.70	60.20
Viscosity @ 100°C (cSt)	7.10	7.36	7.40	10.87	9.487
Viscosity Index	160	151	151	165	140
Flash Point, °C/°F	221/430	>200/392	>200/392	>200/392	>200/392
Pour Point, °C/°F	-43/-45	-39/-38	-39/-38	-39/-38	-39/-38
Cold Cranking Simulator @ °C, cP	-35/6200	-35/5786	-30/3620	-30/3956	-30/3956
API Gravity	34.0	35.3	34.9	34.8	34.8

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap & water should any contact occur. Always follow manufacturers recommendations for fluid viscosity and service category. SUPPLYPRO, LLC assumes no responsibility for product misuse or improper application. For a copy of this product's Safety Data Sheet (SDS) or Technical Data Sheet (TDS), visit www.SUPPLYPRO1.com



SUPPLYPRO, LLC | 115 Empire Way SW, Atlanta, GA 30354 | www.supplypro1.com



OILPRO FULL SYNTHETIC

API SP/GF-6A MULTI-GRADE ENGINE OILS

SAE 0W-16, 0W-20, 5W-20, 5W-30



PRODUCT ORDERING INFORMATION

OILPRO FULL SYNTHETIC ENGINE OILS

<u>01//-15</u>	<u>01/-20</u>	<u>5W-20</u>	<u>51/-30</u>
BULK	BULK	BULK	BULK
00103509200W16116	00103509200W20116	00103509205W20116	00103509205W30116
55G DRUM	55G DRUM	55G DRUM	55G DRUM
00103509200W16089	00103509200W20089	00103509205W20089	00103509205W30089
			-
5G PAIL	5G PAIL	5G PAIL	5G PAIL
00103509200W16081	00103509200W20081	00103509205W20081	00103509205W30081
	1		
6/1 QUART	6/1 QUART	6/1 QUART	6/1 QUART
00103509200W16034	00103509200W20034	00103509205W20034	00103509205W30034



This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap & water should any contact occur. Always follow manufacturers recommendations for fluid viscosity and service category. SUPPLYPRO, LLC assumes no responsibility for product misuse or improper application. For a copy of this product's Safety Data Sheet (SDS) or Technical Data Sheet (TDS), visit www.SUPPLYPRO1.com



SUPPLYPRO, LLC | 115 Empire Way SW, Atlanta, GA 30354 | www.supplypro1.com