#### TECHNICAL DATA SHEET 1/2

# OILPRO FULL SYNTHETIC DEXOS API SP/GF-6A MULTI-GRADE ENGINE OILS SAF 0W-20, 5W-30

# PRODUCT DESCRIPTION

**OILPRO Full Synthetic DEXOS Motor Oil** is our most advanced full synthetic passenger car and light-duty truck engine oil series. Formulated with premium high quality OILPRO base stocks and compounded with a state-of-the-art advanced additive package that delivers superior protection and performance in extreme temperature ranges. OILPRO FS DEXOS is a GM dexos 1<sup>®</sup> Gen3 approved motor oil.

# PRODUCT APPLICATION

OILPRO Full Synthetic DEXOS Motor Oil is recommended for use in a wide range of vehicle & fuel types requiring approved fluids:

- Gasoline and flex fuel (up to E85) passenger cars, light-duty trucks, sport utility vehicles and gasoline-electric hybrids.
- Safely protect engines fitted with turbochargers (including TGDI engines), superchargers & emission control system catalysts.
- Engines and manufacturers specifying an API SP/ILSAC GF-6A or dexos1<sup>®</sup> Gen3 approved engine oil.



#### **SPECIFICATIONS**

- API SP, SN Plus, SN
- ILSAC GF-6A
- dexos1<sup>®</sup> Gen3
  Ford WSS-M2C947-B1
- Chrysler MS-6395
- Ford WSS-M2C962-A1
- Ford WSS-M2C946-B1 GM 4718M & GM 6094M

# TYPICAL TECHNICAL PROPERTIES



# FEATURES AND BENEFITS

OILPRO Full Synthetic DEXOS Motor Oils are formulated to surpass API SP & ILSAC GF-6A industry standards in order to meet the ever-increasing performance and emissions requirements of today's technologically advanced engine systems:

- Protects Turbocharged Gasoline Direct Injection (TGDI) engines that may experience Low-Speed Pre-Ignition (LSPI).
- Improved control of sludge, high temperature deposit formation and viscosity increase than previous generation gasoline engine oils.
- Robust anti-wear & friction control additives help protect timing chains and valvetrains from stretching and surface degradation.
- Maintains more consistent viscosity than previous generation chemistry which helps extend both drain intervals and engine life.
- Helps reduce fuel costs while still providing excellent protection against engine wear under the most extreme operating conditions.
- OILPRO Full Synthetic DEXOS engine oils are backward compatible to previous API and ILSAC specifications.

• OILPRO Full Synthetic DEXOS engine oils 0W-20 and 5W-30 are licensed dexos 1<sup>®</sup> Gen3 fluids.



PROPERTY	TEST METHOD	0W-20	5W-30
Viscosity @ 40°C (cSt)	ASTM D445	39.87	63.70
Viscosity @ 100°C (cSt)	ASTM D445	7.36	10.87
Viscosity Index	ASTM D2270	151	165
Flash Point, °C/°F	ASTM D92	>200/392	>200/392
Pour Point, °C/°F	ASTM D5950	-39/-38	-39/-38
Cold Cranking Simulator @ °C, cP	ASTM D5293	-35/5786	-30/3956
API Gravity	ASTM D287	35.3	34.8

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap & water should any contact occur. Always follow manufacturers recommendations for fluid viscosity and service category. SUPPLYPRO, LLC assumes no responsibility for product misuse or improper application. For a copy of this product's Safety Data Sheet (SDS) or Technical Data Sheet (TDS), visit www.SUPPLYPRO1.com



SUPPLYPRO, LLC | 115 Empire Way SW, Atlanta, GA 30354 | www.supplypro1.com



# OILPRO FULL SYNTHETIC DEXOS

OILPRO

#### PRODUCT ORDERING INFORMATION



This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap & water should any contact occur. Always follow manufacturers recommendations for fluid viscosity and service category. SUPPLYPRO, LLC assumes no responsibility for product misuse or improper application. For a copy of this product's Safety Data Sheet (SDS) or Technical Data Sheet (TDS), visit www.SUPPLYPRO1.com



SUPPLYPRO, LLC | 115 Empire Way SW, Atlanta, GA 30354 | www.supplypro1.com